

SK475



96' MAST

Clear Height 96'

Maximum Static Load:

240,000# Capacity with 6 lines
(Drilling)

250,000# Capacity with 6 lines
(Service / Workover)

Tubing Board Capacity:

60' Double Strands
14,500' - 2 7/8" EUE tubing

Rod Board Capacity:

75' Triple Strands
12,000' - 7/8" sucker rod

Service Depth ----- 14,000'

Workover Depth ----- 10,000'

Drilling Depth ----- 6,000' - 3 1/2" Drill Pipe

Carrier ----- 5 Axles

High Tensile Alloy Wide Flanged Beam

Front Axles: 20,000# Capacity Suspension: Spring

Rear Axles: 46,000# Tandem Suspension: Walking Beam

Push Axle: 25,000# Capacity

Front Tires: 385/65R22.5 Rear Tires: 11R22.5

Power Train

Engine - Series 60 Detroit Diesel -- 475 HP @ 2100 RPM

Transmission - 4500 OFS Allison

Main Drum

Brakes: 42" diameter x 10" wide

Water spray brake cooling

48" Air Cooled Disc Assist

Barrel: 16" diameter x 38.75" wide

Chain: Double 140 Clutch: 224

Shaft: 5.90" Lebus Grooving: 1"

Sand Drum

Brakes: 38" diameter x 8" wide

Water spray brake cooling

Barrel: 12.75" diameter x 40.75" wide

Chain: Double 140 Clutch: 124

Shaft: 4.75"

Capacity: 12,500' - 9/16" or 10,000' - 5/8"

The Macrico logo is located in the bottom right corner of the page. It consists of the word "Macrico" in a bold, white, sans-serif font, set against a background of a blue rectangle on top and a red rectangle on the bottom.