

# SK575



## 104' MAST

Clear Height 104'  
 Maximum Static Load:  
 230,000# Capacity with 6 lines  
 (Drilling)

250,000# Capacity with 6 lines  
 (Service / Workover)

Tubing Board Capacity:  
 60' Double Strands  
 17,000' - 2 7/8" EUE tubing

Rod Board Capacity:  
 75' Triple Strands  
 14,000' - 7/8" sucker rod

Also available with our

## 104' MAST

Clear Height 104'  
 Maximum Static Load:  
 315,000# Capacity w/ 6 lines  
 330,000# Capacity w/ 8 lines

Tubing Board Capacity:  
 60' Double Strands  
 22,000' - 2 7/8" EUE tubing

Rod Board Capacity:  
 75' Triple Strands  
 14,000' - 7/8" sucker rod

Service Depth ----- 16,000'  
 Workover Depth ----- 10,000'  
 Drilling Depth ----- 7,000' - 3 1/2" Drill Pipe

Carrier ----- 5 Axles  
 High Tensile Alloy Wide Flanged Beam  
 Front Axles: 20,000# Capacity      Suspension: Spring  
 Rear Axles: 46,000# Tandem      Suspension: Walking Beam  
 Push Axle: 25,000# Capacity  
 Front Tires: 385/65R22.5      Rear Tires: 11R22.5

Power Train  
 Engine - Series 60 Detroit Diesel -- 475 HP @ 2100 RPM  
 Transmission - 4500 OFS Allison

Main Drum  
 Brakes: 42" diameter x 12" wide  
 Water spray brake cooling  
 Double 48" Air Cooled Disc Assist  
 Barrel: 16" diameter x 38.75" wide  
 Chain: Double 140      Clutch: 324  
 Shaft: 6.60"      Lebus Grooving: 1"

Sand Drum  
 Brakes: 42" diameter x 8" wide  
 Water spray brake cooling  
 Barrel: 16" diameter x 43.75" wide  
 Chain: Double 140      Clutch: 224  
 Shaft: 5.90"  
 Capacity: 14,400' - 9/16" or 11,800' - 5/8"

